

**This Page Is Inserted by IFW Operations
and is not a part of the Official Record**

BEST AVAILABLE IMAGES

**Defective images within this document are accurate representations of
the original documents submitted by the applicant.**

Defects in the images may include (but are not limited to):

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 56109460
PUBLICATION DATE : 29-08-81

APPLICATION DATE : 04-02-80
APPLICATION NUMBER : 55012766

APPLICANT : JAPAN STORAGE BATTERY CO LTD;

INVENTOR : TOKUNAGA AKIO;

INT.CL. : H01M 4/62 H01M 4/20

TITLE : LEAD STORAGE BATTERY

ABSTRACT : PURPOSE: To improve initial properties and durability by adding graphite with strong anisotropy into a positive electrode plate.

CONSTITUTION: Porosity of the active material is increased by adding graphite having strong anisotropy into positive electrode paste to form the positive electrode plate. The addition amount is, for example, about 1% of lead powder. Graphite with strong anisotropy is made by, for example, heating natural graphite at 2,000°C.

COPYRIGHT: (C) JPO